

Addressing Nearshore Placement Near Lake Worth Inlet, FL

Drew Condon, Ph. D., P.E.

Coastal Engineer

Coastal Design Section - SAJ

20 April 2017

*Team of Professionals Making
Tomorrow Better*





Background – Lake Worth Inlet



BUILDING STRONG

- Federally maintained inlet since 1934
 - ▶ North and south jetties, channel, turning basin, inlet revetments, and settling basin
- Final Integrated Feasibility Report and EIS (Jan 2014) report shoaling rates of approximately 117,500 cy/yr
- Beach quality material placed either on the dry beach or in the nearshore below MHW to the -17 ft MLW contour between 500 ft south of R-76 to R-79
- Where is optimal placement?





Wave Climatology



BUILDING STRONG

- To create wave regime in Nearshore: Hypercube method adopted from South Palm Beach Island Comprehensive Shoreline Stabilization Project: EIS by CB&I
 - ▶ Based on WIS data
 - ▶ Offshore dir. Bands generating 95% of the nearshore energy (5° to 155 °)
 - ▶ Six directional bins ~ equal wave energy
 - ▶ Each bin → three height classes ~ equal wave energy in shallow water
 - ▶ 18 wave cases plus calm

Wave Case	Hs (m)	Tp (sec)	Wave Dir. (°)	% Occur. In One Year	Days in Model in One Year
1	0.89	9.35	37.93	5.52	20.15
2	1.13	5.64	119.07	4.11	15.00
3	2.98	10.09	18.06	0.93	3.39
4	1.84	10.10	29.55	1.53	5.58
5	2.06	6.98	74.42	1.11	4.05
6	1.59	7.80	51.83	1.84	6.72
7	1.04	7.60	16.90	8.26	30.15
8	2.54	9.87	37.90	0.67	2.45
9	0.68	5.30	119.89	11.75	42.89
10	1.86	8.72	17.13	2.44	8.91
11	1.92	6.51	121.16	1.17	4.27
12	0.81	7.01	77.08	7.45	27.19
13	2.67	10.84	29.20	0.7	2.56
14	1.68	9.58	38.03	1.57	5.73
15	1.01	8.78	26.61	5.31	19.38
16	2.38	8.56	51.10	0.75	2.74
17	1.37	6.51	76.13	2.91	10.62
18	0.89	8.36	52.20	5.43	19.82
Calm	0.30	6.00	20.00	36.55	133.41







Coastal Modeling System



BUILDING STRONG



Flow

- ▶ Telescoping grid
- ▶ 12.5 m to 800 m resolution

- ▶ 167,232 cells
- ▶ Tidal forcing – NOAA Lake Worth Pier Constituents

Wave

- ▶ 10 m to 200 m resolution

- ▶ 32,538 cells

Elevation

- ▶ PBH surveys
- ▶ Beach profiles
- ▶ AIWW survey

- ▶ Lidar
- ▶ NOAA Palm Beach, FL DEM
- ▶ Referenced to MSL





Calibration / Validation



BUILDING STRONG

- Limited data available
 - ▶ Calibration to water levels:
 - NOAA Port of Palm Beach
 - ▶ Validation with ADCP data
 - Collected over Spring and Neap periods in 2008
- Current magnitude slightly underestimated
 - ▶ Doubled tidal amplitude to “bracket” expected conditions







Calibration / Validation



Spring Tide

Neap Tide

BUILDING STRONG





Production Runs



BUILDING STRONG

- CMS model run for year-long simulations
 - ▶ Both regular tidal constituents and double-amplitude constituents
 - ▶ 3 hour wave coupling
 - ▶ 3 different randomizations of the wave climate with yearly percent occurrence as presented
 - ▶ Total of 6 year long simulations
- Cumulative velocities analyzed to identify nodal point







Nodal Point Analysis



BUILDING STRONG







Nodal Point Analysis



BUILDING STRONG






Nodal Point Analysis




BUILDING STRONG

Regular Amplitude



Double Amplitude





Wave Energy Analysis



BUILDING STRONG

- ~ 120,000 cy/yr should be dredged from the channel and placed in the nearshore
- Four nearshore placement scenarios were developed to replicate placement of approximately 120,000 cy
 - ▶ Alternative 1: Between R-77 and R-78, 4 ft added between the -10 and -17 ft MSL contours
 - ▶ Alternative 2: Between R-77 and R-79, 2.5 ft added between the -10 and -17 ft MSL contours
 - ▶ Alternative 3: Between R-77 and R-79, 4 ft added between the -12 and -17 ft MSL contours
 - ▶ Alternative 4: Between R-78 and R-79, 6 ft added between the -8 and -17 ft MSL contours






Wave Energy Analysis



BUILDING STRONG






Wave Energy Analysis



BUILDING STRONG

- Total cumulative wave energy was estimated as the square of the wave height
- Approximated along a north-south running profile at the -5 ft MSL water depth






Alternatives




BUILDING STRONG

Alt. 1



Alt. 2






Alternatives




BUILDING STRONG

Alt. 3



Alt. 4





Mobilization of Sediment



BUILDING STRONG

- Sediment Mobility Tool applied at 7 different cross-shore depths assuming median grain size, d_{50} , of 0.14 mm

Depth (m)	Linear Wave Theory		Stream Function Wave Theory	
	Freq. of Sediment Mobility	Mean Mobility Score <M>	Freq. of Sediment Mobility	Mean Mobility Score <M _u >
3.04	99.9%	3.61	100%	4.69
4.57	99.9%	2.15	99.9%	3.53
6.10	93.6%	1.45	99.9%	2.84
7.62	93.6%	1.01	99.9%	2.29
9.14	93.5%	0.67	93.6%	1.87
10.67	82.0%	0.43	93.6%	1.53
12.19	41.3%	0.25	93.6%	1.26

- Dean number used to predict cross-shore sediment migration

d_{50} (mm)	Predicted Sediment Migration
0.1	72% Erosive, Offshore Migration
0.14	84% Accretion, Onshore Migration
0.2	97% Accretion, Onshore Migration
0.3	100% Accretion, Onshore Migration
0.4	100% Accretion, Onshore Migration
0.5	100% Accretion, Onshore Migration





Conclusion



BUILDING STRONG

- North – South velocity nodal point located around R-77
 - ▶ Material placed north of this will likely end up in the inlet
 - ▶ Nearshore placement should be confined between R-77 and R-79
- Reduction of wave energy varies by placement layout, between 5 and 75%
 - ▶ Smaller the negative freeboard, the greater the energy reduction
- Sediment is likely to mobilize and move onshore
 - ▶ SMT predicts mobilization is highly probable
 - ▶ Dean number predicts that when mobilized sediment will migrate onshore
- Wave climate randomizations all produced similar average and cumulative current results





Questions



BUILDING STRONG

- Thank you!





References



BUILDING STRONG

- Bonanata, R., R. Medina, L. Silveira, L. Benedet. 2010. *Metodologia para la caracterización del clima marítimo*. In VI Cong. Argentino de Ingenieria Portuaria, 1-14.
- Larson, M. and Kraus, N. C. 1992. *Analysis of cross-shore movement of natural longshore bars and material placed to create longshore bars*. U.S. Army Engineer Waterways Experiment Station, Vicksburg, M.S.: Technical Report DRP-92-5.
- McFall, B. C., S. J. Smith, C. E. Pollock, J. Rosati, III, and K. E. Brutsché. 2016. *Evaluating sediment mobility for siting nearshore berms*. ERDC/CHL CHETN-IV-108. Vicksburg, MS: U.S. Army Engineer Research and Development Center.
- Sanchez, A., W. Weiming, T. M. Beck, H. Li, J. Rosati, III, R. Thomas, J. D. Rosati, Z. Demirbilek, M. Brown, and C. Reed. 2011a. U.S. Army Corps of Engineers Jacksonville District. 2012. *Geotechnical data report for Palm Beach Harbor Maintenance Dredging 33-foot Project, Palm Beach County, Florida*; Section 00 31 32. U.S. Army Corps of Engineers – Geotechnical Branch - Engineering Division - Jacksonville District. Published 20 July 2012.
- U.S. Army Corps of Engineers Jacksonville District. 2014. *Final integrated feasibility report and environmental impact statement: Lake Worth Inlet, Palm Beach Harbor, Palm Beach County, Florida*.
- U.S. Army Corps of Engineers Jacksonville District. 2016. *Southern Palm Beach Island comprehensive shoreline stabilization project*. Final Environmental Impact Statement.

