



Reservoir Sediment Management & Analysis for Engineers

Sediment Bypass Channels and Tunnels


University of Kansas
LEEP2 Building – Room G415
June 11-15, 2018



Sediment Bypass



Sediment bypass at Nagle Dam, South Africa
(Figure from Annandale 2013)



Sediment bypass tunnel at Miwa Dam, Japan
(Figure from Annandale 2011)



Sediment Bypass – Main Channel Storage

- Bypass high sediments flows around reservoir by constructing a large-capacity channel or tunnel
- Topographic conditions are favorable
- Intercept / divert flow upstream of the reservoir pool
- May eliminate the need, or reduce size, for a large-capacity spillway at the main dam since flood flow is diverted



Sediment Bypass Example




FIGURE 13.9 Sediment bypass configuration at Nagle Reservoir in South Africa (*after Annandale, 1987*)




Sediment Bypass – Offstream Storage

- Constructed storage off the main river
- Most sediments continue with the main channel
- Fill with diverted water of low sediment concentration
- Sediment floodwaters can be partially excluded
- Intake designed to exclude coarse sediments
- Construct by dike impoundment in floodplain or small dam on tributary
- Flow into storage is limited by lesser of diversion capacity and stream flow at time of diversion



Sediment Bypass – Offstream Storage Examples



From Morris and Fan, Reservoir Sedimentation Handbook



Sediment Bypass

- PRO


- ▶ Passes sediment during high flows (more natural) maintaining storage volume


- CON

- ▶ Very expensive retrofit for existing facilities
- ▶ Doesn't pass 100% of sediment
- ▶ Not effective in low head elevations & coarse material



Solis Reservoir, Switzerland





Downstream Discharge



Oertli and Auel, 2015

Effectiveness

1987 Flood (No SBT)

- 252 m³/s
- 248,000 m³ deposition

2014 Flood (with SBT)

- 288 m³/s
- 102,000 m³ deposition




Shihmen Reservoir in Taiwan

■ Location

- ▶ Taoyuan County
- ▶ DaHan River
- ▶ Build in 1956-1964

■ Functions

- ▶ Municipal Use & Irrigation
- ▶ Power Generation
- ▶



During Typhoon

Large amount of sediments enters reservoir during large storm

► Photo: during typhoon 海棠(July 2005)



Increased Sediment Supply

- 4 time more than the original estimate
- Impact of 921 Earthquake (in 1999; 2,415 death)
 - ▶ Steep Watershed Valley
 - ▶ Geological Weathering and Climate Change
 - ▶ Landslides and Soil Erosion



Typhoon Aere

- Time: August 23-26, 2004 Rainfall: 973 mm
- Peak Discharge: 8,594 cms Deposit: 27.9 mill-m³
- Reservoir Capacity Loss: 11%
- SSC > 100 g/L for 3 weeks
- Water supply stopped for 17 days




Government Mandates after Aere

- 25 billion NTD (~ 780 million USD)
- Water Supply Ensured (>1 million people)
- Reservoir Life Extended/Sustained




New Bypass Tunnels (Desilting)

- Plan A, B, C and D
- Typical Design: 12m diam; 1600 cms capacity



Bypass Tunnels

- Plan A (1,600 cms) and C: (1,200 cms)



Comparison of Plans

- Percentage of sediment passed through outlets during typhoon Aere

		Bypass Tunnel	Power House	Spillway & Flood Diversion	Perm. Channel	Shihmen Intake	Total Passed
Existing	Numerical	none	30.3%	22.6%	2.42%	0.52%	55.9%
	Physical		29.0%	13.2%	2.36%	0.54%	45.1%
C Tunnel Plan	Numerical	31.4%	25.3%	12.1%	2.10%	0.46%	71.4%
	Physical	31.6%	18.8%	14.7%	1.41%	0.38%	67.0%
A Tunnel Plan	Numerical	35.4%	22.9%	12.6%	1.83%	0.41%	73.0%
	Physical	31.4%	22.8%	13.0%	1.78%	0.38%	69.4%



Tseng-wen Sediment Sluicing Tunnel (or bypass or venting)






16/05/2016 01:59






16/05/2016 02:16






16/05/2016 02:27





16/05/2016 02:27






16/05/2016 02:54



Questions?



16/05/2016 03:11

